Software and other **Accessories**



Software FlukeView[®] Forms

FlukeView Forms increases the power of your Fluke tool by enabling you to document, store and analyze individual readings or series of measurements, then convert them into professional-looking documents. FlukeView Forms supports the following multimeters:



Hanging & Locking Kits

ToolPak (TPAK)

- The meter hanging solution
- Kit includes, universal hanger clips (2), hook & loop straps (2 lengths) and strong magnet
- Combine components to meet most hanging needs

See page 106 for compatibility chart

FlukeView Forms Compatibility Chart

FVF Option	Instrument	Cable**	Application Level
FVF-UG	Software only upgrade, Fluke 568, 975, 983	No Cable included	
FVF-SC1	Fluke 53-II, 54-II, 87-IV*, 89-IV*	Serial / IRDA	FVF Full (includes Designer)
FVF-SC2	Fluke 280 Series, 789, 1550B, 1653, 180 Series*	USB / IR	
FVF-SC4	Fluke 8808A, 8845A, 8846A, 45*	USB / Serial	
FVF-BASIC	Fluke 280 Series, 789, 1550B, 1653, 180 Series*	USB / IR	FVF BASIC
FVF-SC5	8808A, 8845A, 8846A, 45*	USB / Serial	

* Obsolete

** USB cables are not supported for Microsoft Windows NT 4.0

IR189USB

IR to USB interface cable

- (included with FVF-SC2 and FVF-Basic)
- · For customers who want to upgrade from
- their existing RS232 cable • Small adapter to connect the cable to the
- 189, 287, 289, 1653 or the 1550B is included.
- · CD-Rom with drivers for use with older versions of FVF-SC1 included.

Make extended logging easier

BP189 High Capacity Battery Enclosure

- (for Fluke 180 Series DMM)
- Expand the battery life of your Fluke 187/189 up to 450 hours (over two weeks of continuous use).
- Houses 4 'C' cell batteries.
- CAT III 1000 V, CAT IV 600 V
- Batteries and meter sold separately





LockPak (LPAK)

- The meter locking solution Kit includes a locking
- accessory Accepts most common
- locks (not included)

See page 106 for compatibility chart



Fiber Optics

FOM Fiber Optic Meter

The Fluke Fiber Optic Meter (FOM) helps you test and maintain fiber optic cables without having to buy a whole new

meter. Plug the FOM directly into any DMM with a mV dc function and a 10 $\,$ MK input impedance and quickly and accurately verify fiber optic cable system loss. Light sources and patch cords sold separately.



FOS 850 & FOS 850/1300 **Fiber Optic Light Sources**

A variety of light sources allow you to test different cable lengths.